



Bearing No. 16002

r	0.3
d	15 mm
D	32 mm
B	8 mm
C	8 mm
fo	13.9
D_	32
B_	8
ra	0.3
Z_	9
C0	2.83
DI_	18.738
SRE	2.46
D_a	30
DE_	28.262
SRI	2.46
DA_	4.762
SREN	-0.015
Noun	Bearing
SRIN	-0.015
bomp	0
SRIX	0.015
yobi	16002
mass	0.027
SDM_	23.5
KBRG	6101
SREX	0.015
SBRG	0
Bore	0.591 Inch 15 Millimeter

r min.	0,3 mm
UNSPSC	31171504
ALPHA_	0
LangID	1
C_conv	5600
da min	17
Weight	0,027 Kg
ra max.	0,3 mm
Oil rpm	28000
da min.	17 mm
hidYobi	16002
Da max.	30 mm
GRS rpm	24000
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Enclosure	Open
Snap Ring	No
Size (mm)	15x32x8
Prod_Type3	DGBB_SR_OT
bore type:	Round
Width (mm)	8
Weight / LBS	0.044
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	16002
Keyword String	Ball
overall width:	8 mm
bore diameter:	15 mm
Precision Class	ABEC 1 ISO P0

Rolling Element	Ball Bearing
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	1.26 Inch 32 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Long Description	15MM Bore; 32MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
outside diameter:	32 mm
Weight / Kilogram	0.02
Manufacturer Name	NSK
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
Outer Diameter (mm)	32
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	28 000 r/min
manufacturer upc number:	029176059377
Internal Special Features	No
(Grease) Lubrication Speed	24 000 r/min
Basic static load rating (C0)	2,83 kN
Basic dynamic load rating (C)	5,6 kN
Maximum Capacity / Filling Slot	No