



Bearing No. 22238 CCK/W33 + H 3138

D	340 mm
B	92 mm
b	16.7 mm
K	9 mm
Size (mm)	340x170x92
Width (mm)	92
d ₃	240 mm
d ₁	170 mm
B ₄	30.5 mm
B ₁	141 mm
d ₁	170 mm
d ₂	225 mm
D ₁	294 mm
B ₁	141 mm
B ₄	30.5 mm
d ₃	240 mm
Bearing number	22238 CCK/W33 + H 3138
Limiting speed	2400 r/min
Reference speed	1700 r/min
Bore Diameter (mm)	340
r _a max.	3 mm
B _a min.	21 mm
D _a max.	323 mm
d _b min.	202 mm
d _a max.	225 mm
Outer Diameter (mm)	170
Calculation factor e	0.26
r _{1,2} min.	4 mm

r_a - max.	3 mm
B_a - min.	21 mm
D_a - max.	323 mm
d_b - min.	202 mm
d_a - max.	225 mm
d_2 ?	225 mm
Mass bearing + sleeve	46 kg
D_1 ?	294 mm
Calculation factor - e	0.26
$r_{1,2}$ - min.	4 mm
Basic dynamic load rating C	1342 kN
Basic dynamic load rating - C	1342 kN
Fatigue load limit P_u	150 kN
Calculation factor Y_1	2.6
Calculation factor Y_2	3.9
Calculation factor Y_0	2.5
Calculation factor - Y_1	2.6
Calculation factor - Y_2	3.9
Fatigue load limit - P_u	150 kN
Basic static load rating C_0	1700 kN
Basic static load rating - C_0	1700 kN