



Bearing No. 24022CK30E4

r	2
d	110 mm
D	170 mm
B	60 mm
C	60 mm
e	0.32
B_	60
C0	645
D_	170
Y2	3.1
Y0	2.1
ra	2
Y1	2.1
X0	1
X1	1
X2	0.67
Y3	2.1
Z_	24
DE_	154.499
DA_	15
SIR	24
DI_	125.164
ALP1	12
SDM_	139.832
ALP2	5
bomp	24022CK30E4
ALP3	0
yobi	24022CK30E4
SBRG	40
KBRG	2322

Da min	148 mm
da min	120
LangID	1
ALPHA_	0.211
r min.	2 mm
Weight	4,96 Kg
da max	121 mm
hidYobi	24022CK30E4
D_a max	160
da min.	120 mm
ra max.	2 mm
D_a min	148
Da max.	160 mm
TSR rpm	2800
GRS rpm	1600
Oil rpm	2200
hidTable	ecat_NSSPHR
Macha rpm	0
Size (mm)	110x170x60
Width (mm)	60
Prod_Type3	SRB_CTB_TB
Bearing number	24022CK30E4
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Calculation factor (e)	0,32
Calculation factor (Y0)	2,1
(Oil) Lubrication Speed	2200 r/min
Calculation factor (Y2)	3,1
(Grease) Lubrication Speed	1600 r/min
Basic dynamic load rating (C)	380 kN
Basic static load rating	645 kN

(C0)	
------	--