



Bearing No. 23128 CCK/W33 + H 3128

D	225 mm
B	68 mm
b	8.3 mm
K	4.5 mm
Size (mm)	225x125x68
Width (mm)	68
d <sub>3</sub>	180 mm
d <sub>1</sub>	125 mm
B <sub>4</sub>	24 mm
B <sub>1</sub>	97 mm
d <sub>1</sub>	125 mm
d <sub>2</sub>	159 mm
D <sub>1</sub>	197 mm
B <sub>1</sub>	97 mm
B <sub>4</sub>	24 mm
d <sub>3</sub>	180 mm
Bearing number	23128 CCK/W33 + H 3128
Limiting speed	2800 r/min
Reference speed	2200 r/min
Bore Diameter (mm)	225
r <sub>a</sub> max.	2 mm
B <sub>a</sub> min.	8 mm
D <sub>a</sub> max.	213 mm
d <sub>b</sub> min.	149 mm
d <sub>a</sub> max.	159 mm
Outer Diameter (mm)	125
Calculation factor e	0.28
r <sub>1,2</sub> min.	2.1 mm

$r_a$ - max.	2 mm
$B_a$ - min.	8 mm
$D_a$ - max.	213 mm
$d_b$ - min.	149 mm
$d_a$ - max.	159 mm
$d_2$ ?	159 mm
Mass bearing + sleeve	14.3 kg
$D_1$ ?	197 mm
Calculation factor - e	0.28
$r_{1,2}$ - min.	2.1 mm
Basic dynamic load rating C	659 kN
Basic dynamic load rating - C	659 kN
Fatigue load limit $P_u$	88 kN
Calculation factor $Y_1$	2.4
Calculation factor $Y_2$	3.6
Calculation factor $Y_0$	2.5
Calculation factor - $Y_1$	2.4
Calculation factor - $Y_2$	3.6
Fatigue load limit - $P_u$	88 kN
Basic static load rating $C_0$	900 kN
Basic static load rating - $C_0$	900 kN