



Bearing No. PCZ 5660 M

D	93,663 mm
d	88,9 mm
B	95,25 mm
M	6 mm
Weight	0,45 Kg
c1 min	0,2 mm
c2 min	1,2 mm
Size (mm)	88.9x93.663x95.25
Width (mm)	95,25
Mass bushing	0.45 kg
? ±8	20 °
Bearing number	PCZ 5660 M
c ₂ max.	2.4 mm
c ₁ min.	0.2 mm
c ₁ max.	1 mm
c ₂ min.	1.2 mm
Bore Diameter (mm)	88,9
Outer Diameter (mm)	93,663
Housing bore range min.	93.662 mm
Housing bore range max.	93.698 mm
Shaft diameter range min.	88.448 mm
Shaft diameter range max.	88.504 mm
Basic dynamic load rating (C)	1000 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	1000 kN
Basic static load rating - radial direction C_0	2080 kN
Factor depending on material and bearing type K_M	1900