



Bearing No. PCZ 6476 E

D	106,363 mm
d	101,6 mm
B	120,65 mm
M	– mm
Weight	0,715 Kg
c1 min	0,2 mm
c2 min	1,2 mm
Size (mm)	101.6x106.363x120.65
Width (mm)	120,65
Mass bushing	0.71 kg
? ±8	20 °
Bearing number	PCZ 6476 E
c ₂ max.	2.4 mm
c ₁ min.	0.2 mm
c ₁ max.	1 mm
c ₂ min.	1.2 mm
Bore Diameter (mm)	101,6
Outer Diameter (mm)	106,363
Housing bore range min.	106.319 mm
Housing bore range max.	106.355 mm
Shaft diameter range min.	101.544 mm
Shaft diameter range max.	101.6 mm
Basic dynamic load rating (C)	965 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	965 kN
Basic static load rating - radial direction C_0	3050 kN
Factor depending on material and bearing type K_M	480