




Bearing No. PCZ 4440 M

D	74,613 mm
d	69,85 mm
B	63,5 mm
M	6 mm
Weight	0,235 Kg
c1 min	0,2 mm
c2 min	1,2 mm
Size (mm)	69.85x74.613x63.5
Width (mm)	63,5
Mass bushing	0.23 kg
? ±8	20 °
Bearing number	PCZ 4440 M
c ₂ max.	2.4 mm
c ₁ min.	0.2 mm
c ₁ max.	1 mm
c ₂ min.	1.2 mm
Bore Diameter (mm)	69,85
Outer Diameter (mm)	74,613
Housing bore range min.	74.612 mm
Housing bore range max.	74.643 mm
Shaft diameter range min.	69.426 mm
Shaft diameter range max.	69.472 mm
Basic dynamic load rating (C)	530 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	530 kN
Basic static load rating - radial direction C_0	1100 kN
Factor depending on material and bearing type K_M	1900