



**Bearing No. ASTT90 F13080**

|   |  |
|---|--|
| Material  | Wrapped bronze with lubrication holes. |
| Bearing Type  | flanged                                |
| Bearing number  | ASTT90 F13080                          |
| Bore Diameter (mm)                                    | 130                                    |
| Outer Diameter (mm)                                   | 135                                    |
| Flange Radius (rfl)                                   | 2.000                                  |
| Wall Thickness (S3)                                   | 2.500                                  |
| OD Chamfer Length (Co)                                | 1.800                                  |
| ID Chamfer Length (Ci)                                | 0.600                                  |
| Flange Thickness (Sfl)                                | 2.500                                  |
| Shaft Dia., Nominal (d)                               | 130.0000                               |
| Flange Dia. (Dfl pm 0.5)                              | 155.000                                |
| ID Chamfer Angle (B deg.)                             | 45                                     |
| Bearing Length, Nominal (B)                           | 80.000                                 |
| Shaft Size (ds) - 130<br>-0.190 / -0.242              | 130 0.190 / 0.242                      |
| Bearing Outside Diameter, Nominal(Do)                 | 135.000                                |
| Housing Bore Dia. (Dh) -<br>135 +0.040 / -0           | 135 +0.040 / 0                         |
| Bearing Length Tolerance (B tol.) - +0 /<br>-0.40     | +0 / 0.40                              |
| Bearing Bore after Mounting (di) - 135<br>+0.100 / -0 | 135 +0.100 / 0                         |