




Bearing No. PCZ 2828 M

D	49,213 mm
d	44,45 mm
B	44,45 mm
M	5 mm
Weight	0,11 Kg
c1 min	0,2 mm
c2 min	1,2 mm
Size (mm)	44.45x49.213x44.45
Width (mm)	44,45
Mass bushing	0.11 kg
? ±8	20 °
Bearing number	PCZ 2828 M
c ₂ max.	2.4 mm
c ₁ min.	0.2 mm
c ₁ max.	1 mm
c ₂ min.	1.2 mm
Bore Diameter (mm)	44,45
Outer Diameter (mm)	49,213
Housing bore range min.	49.212 mm
Housing bore range max.	49.238 mm
Shaft diameter range min.	44.112 mm
Shaft diameter range max.	44.153 mm
Basic dynamic load rating (C)	232 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	232 kN
Basic static load rating - radial direction C_0	490 kN
Factor depending on material and bearing type K_M	1900