



Bearing No. PCZ 2228 M

D	38,894 mm
d	34,925 mm
B	44,45 mm
M	4 mm
Weight	0,069 Kg
c1 min	0,1 mm
c2 min	0,8 mm
Size (mm)	34.925x38.894x44.45
Width (mm)	44,45
Mass bushing	0.069 kg
? ±8	20 °
Bearing number	PCZ 2228 M
c ₂ max.	1.6 mm
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.8 mm
Bore Diameter (mm)	34,925
Outer Diameter (mm)	38,894
Housing bore range min.	38.895 mm
Housing bore range max.	38.918 mm
Shaft diameter range min.	34.592 mm
Shaft diameter range max.	34.633 mm
Basic dynamic load rating (C)	183 kN
Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2.5 m/s

velocity v max.	
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	183 kN
Basic static load rating - radial direction C_0	380 kN
Factor depending on material and bearing type K_M	1900