



Bearing No. PCZ 2432 E

D	42,069 mm
d	38,1 mm
B	50,8 mm
M	– mm
Weight	0,096 Kg
c1 min	0,1 mm
c2 min	0,8 mm
Size (mm)	38.1x42.069x50.8
Width (mm)	50,8
Mass bushing	0.096 kg
? ±8	20 °
Bearing number	PCZ 2432 E
c ₂ max.	1.6 mm
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.8 mm
Bore Diameter (mm)	38,1
Outer Diameter (mm)	42,069
Housing bore range min.	42.057 mm
Housing bore range max.	42.083 mm
Shaft diameter range min.	38.029 mm
Shaft diameter range max.	38.07 mm
Basic dynamic load rating (C)	153 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	153 kN
Basic static load rating - radial direction C_0	475 kN
Factor depending on material and bearing type K_M	480