




Bearing No. PCZ 2624 E

D	45,244 mm
d	41,275 mm
B	38,1 mm
M	– mm
Weight	0,078 Kg
c1 min	0,1 mm
c2 min	0,8 mm
Size (mm)	41.275x45.244x38.1
Width (mm)	38,1
Mass bushing	0.078 kg
? ±8	20 °
Bearing number	PCZ 2624 E
c ₂ max.	1.6 mm
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.8 mm
Bore Diameter (mm)	41,275
Outer Diameter (mm)	45,244
Housing bore range min.	45.232 mm
Housing bore range max.	45.258 mm
Shaft diameter range min.	41.204 mm
Shaft diameter range max.	41.245 mm
Basic dynamic load rating (C)	122 kN
Specific dynamic load factor K	80 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding	2 m/s

velocity v max.	
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	122 kN
Basic static load rating - radial direction C_0	380 kN
Factor depending on material and bearing type K_M	480