



Bearing No. BK2212

	IR17X22X13 / Suitable inner ring
m	18 g / Weight
D	28 mm
Noun	Bearing
Bore	0.866 Inch 22 Millimeter
Width	0.472 Inch 12 Millimeter
UNSPSC	31171512
Category	Needle Non Thrust Roller Bearing
Retainer	Yes
Inventory	0.0
Enclosure	Open
Component	Roller Assembly with Outer Ring - No Inner Ring
Separable	No
Size (mm)	22x28x12
Closed End	Yes
Width (mm)	12
Weight / LBS	0.033
Self Aligning	No
Product Group	B04144
n_G	11700 1/min / Limiting speed
Inch - Metric	Metric
F_w	22 mm
n_B	8300 1/min / Reference speed
C_r	9100 N / Dynamic load rating (radial)

Relubricatable	No
Thrust Bearing	No
Other Features	1 Rib Outer Ring Drawn Cup Bearing Steel Cage
Keyword String	Needle
Bearing number	BK2212
C_{Or}	13400 N / Static load rating (radial)
C_{ur}	1600 N / Fatigue limit load, radial
Rolling Element	Needle Roller Bearing
r_{min}	0,8 mm
Long Description	22MM Bore; 28MM Outside Diameter; 12MM Width; Needle Roller Bearing; Roller Assembly with Outer Ring - No Inner Ring; Open Enclosure; No Self Aligning; Retainer; Single Row of Rollers; No Separable; C
Outside Diameter	1.102 Inch 28 Millimeter
Manufacturer URL	http://www.ina.com
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	0.023
$C_{t\ min}$	9,3 mm
Bore Diameter (mm)	22
Outer Diameter (mm)	28
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	BK2212
Number of Rows of Rollers	Single Row

C - 12 mm / Tolerance: -0,3	12 mm / Tolerance: 0,3
--------------------------------	------------------------