



Bearing No. 24780/24720

e	0.39
d	41,275 mm
D	76,2 mm
T	22,225 mm
B	23,02 mm
C	17,462 mm
a	17 mm
Da	68 mm
B_	23.02
Db	72 mm
da	53 mm
Y0	0.84
db	47,5 mm
C0	82
D_	76.2
Z_	18
C_	17.462
Y1	1.5
DE_	65.495
SLR	16
D_a	68
DI_	49.757
DA1	8.877
DA2	7.857
CUP	0.15
DA_	8.37
D_b	72
RAr	138.739
SDM_	58.004
KBRG	3161

yobi	24780/24720
CONE	0.279
ALP21	29
ALP22	18
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	40
r min.	3,5 mm
LangID	1
Weight	0,429 Kg
ALPHA_	14.65
r1 min.	0,8 mm
ra max.	3,5 mm
Oil rpm	6700
outer r	0.8
hidYobi	24780/24720
GRS rpm	4800
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	0.8
ra1 max.	0,8 mm
Size (mm)	41.275x76.2x22.225
SHOG_yobi	24780R/24720R
Prod_Type3	TRBSR_ID_A
Width (mm)	22,225
Bearing number	24780/24720
Bore Diameter (mm)	41,275
Outer Diameter (mm)	76,2
Calculation factor (e)	0,39

(Oil) Lubrication Speed	6700 r/min
Calculation factor (Y0)	0,84
(Grease) Lubrication Speed	4800 r/min
Basic static load rating (C0)	82 kN
Basic dynamic load rating (C)	66 kN