



Bearing No. PFT 15 FM

H	7.1 mm
N	7.1 mm
d	15 mm
T	24.6 mm
L	59 mm
J	63 mm
Size (mm)	15x2x7
Width (mm)	7
A ₁	2 mm
A ₂	7 mm
B ₁	28.6 mm
S ₁	22.6 mm
B ₄	4.75 mm
B ₄	4.75 mm
B ₁	28.6 mm
A ₂	7 mm
A ₁	2 mm
S ₁	22.6 mm
Bearing number	PFT 15 FM
Limiting speed	9500 r/min
Housing material	Pressed steel
Mass bearing unit	0.2 kg
D _a min.	44 mm
Bore Diameter (mm)	15
Outer Diameter (mm)	2
D _a - min.	44 mm
Thread - G ₂	M6x0.75
Basic dynamic load rating C	9.56 kN

Basic dynamic load rating - C	9.6 kN
Thread grub screw G ₂	M6x0.75
Fatigue load limit P _u	0.2 kN
Fatigue load limit - P _u	0.2 kN
Hexagonal key size for grub screw N	3 mm
Hexagonal key size for grub screw - H	3 mm
Basic static load rating C ₀	4.75 kN
Basic static load rating - C ₀	4.8 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	6 mm
Recommended diameter for attachment bolts, inch G	0.25 in