



### Bearing No. PFT 25 TF

N	8,7 mm
G	8 mm
T	21,8 mm
L	71 mm
H	95 mm
J	76 mm
B	34,1 mm
d	25 mm
A1	2 mm
Da	60 mm
H1	– mm
A2	9 mm
Weight	0,28 Kg
Category	Mounted Units & Inserts
Inventory	0.0
Width (mm)	34,1
B <sub>4</sub>	5 mm
A <sub>1</sub>	2 mm
Product Group	M06110
A <sub>2</sub>	9 mm
s <sub>1</sub>	19.8 mm
Bearing number	PFT 25 TF
Limiting speed	7000 r/min
Housing material	Pressed steel
Mass bearing unit	0.28 kg
Manufacturer Name	SKF
Weight / Kilogram	0.18
D <sub>a</sub> min.	56 mm
Bore Diameter (mm)	25
Minimum Buy Quantity	N/A

Basic dynamic load rating C	14 kN
Basic static load rating (C <sub>0</sub> )	7,8 kN
Basic dynamic load rating (C)	14 kN
Thread grub screw G <sub>2</sub>	M6x0.75
Fatigue load limit P <sub>u</sub>	0.335 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating C <sub>0</sub>	7.8 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	8 mm
Recommended diameter for attachment bolts, inch G	0.3125 in