



**Bearing No. PFT 25 WF**

H	8.7 mm
N	8.7 mm
d	25 mm
T	28.9 mm
L	71 mm
J	76.2 mm
Size (mm)	25x2x9
Width (mm)	9
A <sub>1</sub>	2 mm
A <sub>2</sub>	9 mm
B <sub>1</sub>	44.4 mm
s <sub>1</sub>	26.9 mm
B <sub>4</sub>	4.75 mm
B <sub>4</sub>	4.75 mm
B <sub>1</sub>	44.4 mm
A <sub>2</sub>	9 mm
A <sub>1</sub>	2 mm
s <sub>1</sub>	26.9 mm
Bearing number	PFT 25 WF
Limiting speed	7000 r/min
Housing material	Pressed steel
Mass bearing unit	0.35 kg
D <sub>a</sub> min.	56 mm
Bore Diameter (mm)	25
Outer Diameter (mm)	2
D <sub>a</sub> - min.	56 mm
Thread - G <sub>2</sub>	M6x0.75
Basic dynamic load rating C	14 kN

Basic dynamic load rating - C	14 kN
Thread grub screw G <sub>2</sub>	M6x0.75
Fatigue load limit P <sub>u</sub>	0.335 kN
Fatigue load limit - P <sub>u</sub>	0.335 kN
Hexagonal key size for grub screw N	3 mm
Hexagonal key size for grub screw - H	3 mm
Basic static load rating C <sub>0</sub>	7.8 kN
Basic static load rating - C <sub>0</sub>	7.8 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	8 mm
Recommended diameter for attachment bolts, inch G	0.3125 in