



**Bearing No. PFT 30 RM**

N	10,5 mm
J	90,5 mm
d	30 mm
T	23,5 mm
L	84 mm
B	30,2 mm
G	10 mm
H	112 mm
A2	9,5 mm
H1	– mm
A1	2,5 mm
Da	71 mm
Weight	0,41 Kg
Width (mm)	30,2
A <sub>1</sub>	2.5 mm
s <sub>1</sub>	21 mm
B <sub>4</sub>	5 mm
A <sub>2</sub>	9.5 mm
Bearing number	PFT 30 RM
Limiting speed	6300 r/min
Housing material	Pressed steel
Mass bearing unit	0.4 kg
D <sub>a</sub> min.	67 mm
Bore Diameter (mm)	30
Basic dynamic load rating C	19.5 kN
Basic static load rating (C0)	11,2 kN
Basic dynamic load rating (C)	19,5 kN
Thread grub screw G <sub>2</sub>	M6x0.75

Fatigue load limit $P_u$	0.475 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating $C_0$	11.2 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in