



Bearing No. PFT 30 WF

| | |
|----------------------------------|---------------|
| L | 84 mm |
| d | 30 mm |
| G | 10 mm |
| H | 112 mm |
| J | 90,5 mm |
| N | 10,5 mm |
| T | 32,6 mm |
| Da | 71 mm |
| A1 | 2,5 mm |
| B1 | 48,4 mm |
| H1 | – mm |
| A2 | 9,5 mm |
| Weight | 0,52 Kg |
| B ₄ | 5.95 mm |
| B ₁ | 48.4 mm |
| A ₁ | 2.5 mm |
| s ₁ | 30.1 mm |
| A ₂ | 9.5 mm |
| Limiting speed | 6300 r/min |
| Bearing number | PFT 30 WF |
| Housing material | Pressed steel |
| Mass bearing unit | 0.55 kg |
| D _a min. | 67 mm |
| Bore Diameter (mm) | 30 |
| Basic dynamic load rating C | 19.5 kN |
| Basic static load rating (C0) | 11,2 kN |
| Basic dynamic load rating (C) | 19,5 kN |
| Thread grub screw G ₂ | M8x1 |

| | |
|---|----------|
| Fatigue load limit P_u | 0.475 kN |
| Hexagonal key size for grub screw N | 4 mm |
| Basic static load rating C_0 | 11.2 kN |
| Recommended tightening torque for grub screw | 6.5 N·m |
| Recommended diameter for attachment bolts, mm G | 10 mm |
| Recommended diameter for attachment bolts, inch G | 0.375 in |