



### Bearing No. PFT 35 TR

N	11 mm
J	100 mm
d	35 mm
T	27,9 mm
L	94 mm
B	42,9 mm
G	10 mm
H	122 mm
A2	10 mm
H1	– mm
A1	2,5 mm
Da	81 mm
Weight	0,65 Kg
Width (mm)	42,9
A <sub>1</sub>	2.5 mm
s <sub>1</sub>	25.4 mm
B <sub>4</sub>	6 mm
A <sub>2</sub>	10 mm
Bearing number	PFT 35 TR
Limiting speed	3200 r/min
Housing material	Pressed steel
Mass bearing unit	0.61 kg
D <sub>a</sub> min.	77 mm
Bore Diameter (mm)	35
Basic dynamic load rating C	25.5 kN
Basic static load rating (C0)	15,3 kN
Basic dynamic load rating (C)	25,5 kN
Thread grub screw G <sub>2</sub>	M6x0.75

Fatigue load limit $P_u$	0.655 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating $C_0$	15.3 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in