



### Bearing No. PFT 35 WF

L	94 mm
d	35 mm
G	10 mm
H	122 mm
J	100 mm
N	11 mm
T	34,8 mm
Da	81 mm
A1	2,5 mm
B1	51,1 mm
H1	– mm
A2	10 mm
Weight	0,8 Kg
B <sub>4</sub>	6.75 mm
B <sub>1</sub>	51.1 mm
A <sub>1</sub>	2.5 mm
s <sub>1</sub>	32.3 mm
A <sub>2</sub>	10 mm
Limiting speed	5300 r/min
Bearing number	PFT 35 WF
Housing material	Pressed steel
Mass bearing unit	0.75 kg
D <sub>a</sub> min.	77 mm
Bore Diameter (mm)	35
Basic dynamic load rating C	25.5 kN
Basic static load rating (C0)	15,3 kN
Basic dynamic load rating (C)	25,5 kN
Thread grub screw G <sub>2</sub>	M10x1

Fatigue load limit $P_u$	0.655 kN
Hexagonal key size for grub screw N	5 mm
Basic static load rating $C_0$	15.3 kN
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in