



Bearing No. 51414

C	252
r	2
d	70 mm
D	150 mm
T	60 mm
D1	73 mm
da	118
ra	2
B_	60
C0	555
d1	150 mm
D_	150
T_	60
Z_	11
DA_	28.575
SRE	15.4
D_a	102
D_1	73
SRI	15.4
KBRG	5111
SREN	0
Noun	Bearing
SRIX	0.1
SRIN	0
mass	5.05
SDM_	110
SREX	0.1
yobi	51414
r min.	2 mm
Banded	No

Weight	5,05 Kg
LangID	1
Bore 1	2.756 Inch 70 Millimeter
Height	2.362 Inch 60 Millimeter
UNSPSC	31171552
Bore 2	2.874 Inch 73 Millimeter
Oil rpm	1500
da min.	118 mm
GRS rpm	1000
ra max.	2 mm
Da max.	102 mm
hidYobi	51414
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	70x150x60
Inventory	0.0
Width (mm)	60
Prod_Type3	TB_SD_WFS
Weight / LBS	11.13334
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	51414
overall width:	60 mm
Keyword String	Ball Thrust
Thrust Bearing	Yes
bore diameter:	70 mm
Other Features	Single Row With Flat Seat
Rolling Element	Ball Bearing

Precision Class	Non-Precision
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	5.906 Inch 150 Millimeter
Long Description	70MM Bore 1; 73MM Bore 2; 150MM Outside Diameter; 60MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Manufacturer Name	NSK
Weight / Kilogram	5.11
outside diameter:	150 mm
Bore Diameter (mm)	70
Outer Diameter (mm)	150
thrust bearing type:	Single-Direction
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
manufacturer upc number:	029176087356
Manufacturer Item Number	51414
Single or Double Direction	Single Direction
(Grease) Lubrication Speed	1000 r/min
Basic static load rating (C0)	555 kN
Basic dynamic load rating (C)	252 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter