




Bearing No. PCMF 060808 E

D	8 mm
d	6 mm
B	8 mm
B1	1 mm
D1	12 mm
r max	1 mm
r max.	1 mm
c1 min	0,1 mm
c2 min	0,2 mm
Weight	0,0019 Kg
Size (mm)	6x8x8
Width (mm)	8
Mass bushing	0.0019 kg
? ±8	20 °
D ₁	12 mm
B ₁	1 mm
Bearing number	PCMF 060808 E
Tolerance shaft	f7
Tolerance housing	H7
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.2 mm
c ₂ max.	1 mm
Bore Diameter (mm)	6
Outer Diameter (mm)	8
Dynamic load rating axial (C)	2,75 kN
Specific dynamic load factor K	80 N/mm ²
Static load rating radial (C0)	9 kN

Dynamic load rating radial (C)	2,9 kN
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2 m/s
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Specific static load factor K_0	250 N/mm ²
Basic dynamic load rating - radial direction C	2.9 kN
Basic dynamic load rating - axial direction C_a	2.75 kN
Basic static load rating - axial direction C_{0a}	8.65 kN
Basic static load rating - radial direction C_0	9 kN
Factor depending on material and bearing type K_M	480