



Bearing No. LM11749/LM11710

e	0.29
d	17,462 mm
D	39,878 mm
T	13,843 mm
B	14,605 mm
C	10,668 mm
a	8,7 mm
Da	34 mm
B_	14.605
Db	37 mm
da	23 mm
Y0	1.2
db	21,5 mm
C0	22.5
D_	39.878
Z_	14
C_	10.668
Y1	2.1
DE_	33.957
SLR	9.3
D_a	34
DI_	23.239
DA1	5.712
DA2	5.157
CUP	0.028
DA_	5.436
D_b	37
RAr	95.34
SDM_	28.635
KBRG	3161

yobi	LM11749/LM11710
CONE	0.055
ALP21	21
ALP22	36
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	26
r min.	1,3 mm
LangID	1
Weight	0,083 Kg
ALPHA_	10.8
r1 min.	1,3 mm
ra max.	1,3 mm
Oil rpm	13000
outer r	1.3
hidYobi	LM11749/LM11710
GRS rpm	10000
inner r	1.3
hidTable	ecat_NSTPRI
inner ra	1.3
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	17.462x39.878x13.843
SHOG_yobi	LM11749R/LM11710R
Prod_Type3	TRBSR_ID_A
Width (mm)	13,843
Bearing number	LM11749/LM11710
Bore Diameter (mm)	17,462
Outer Diameter (mm)	39,878
Calculation factor (e)	0,29

(Oil) Lubrication Speed	13000 r/min
Calculation factor (Y0)	1,2
(Grease) Lubrication Speed	10000 r/min
Basic static load rating (C0)	22,5 kN
Basic dynamic load rating (C)	22,5 kN