



**Bearing No. PWKRE 47.2RS**

G	M 20x1.5
C	24 mm
c	1 mm
M	6 mm
D	47 mm
d	24 mm
B	66 mm
SW	10 mm
Category	Bearings
Inventory	0.0
Size (mm)	24x47x66
Width (mm)	66
B <sub>1</sub>	40.5 mm
d <sub>1</sub>	27 mm
Product Group	B04144
B <sub>1</sub>	40.5 mm
B <sub>2</sub>	9 mm
B <sub>3</sub>	18 mm
C <sub>1</sub>	0.8 mm
M <sub>1</sub>	4 mm
B <sub>2</sub>	9 mm
G <sub>1</sub>	21 mm
M <sub>1</sub>	4 mm
G <sub>1</sub>	21 mm
Hexagonal nut	M 20x1.5
d <sub>1</sub>	27 mm
C <sub>1</sub>	0.8 mm
B <sub>3</sub>	18 mm
Bearing number	PWKRE 47.2RS

Limiting speed	3800 r/min
Grease fitting	NIP A2x7.5
Mass cam follower	0.4 kg
Manufacturer Name	SKF
Weight / Kilogram	0
Bore Diameter (mm)	24
Outer Diameter (mm)	47
Lubrication adapter	AP 10
Mass support roller	0.4 kg
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	1 mm
$r_{1,2}$ - min.	1 mm
Basic dynamic load rating C	22.9 kN
Basic dynamic load rating - C	22.9 kN
Recommended tightening torque	120 N·m
Fatigue load limit $P_u$	2.8 kN
Fatigue load limit - $P_u$	2.8 kN
Basic static load rating $C_0$	24.5 kN
Basic static load rating - $C_0$	24.5 kN
Maximum dynamic radial loads - $F_r$	18.3 kN
Maximum static radial loads - $F_{0r}$	26 kN
Maximum dynamic radial loads $F_r$ max.	18.3 kN
Maximum static radial loads $F_{0r}$ max.	26 kN