



Bearing No. 25590/25520

e	0.33
d	45,618 mm
D	82,931 mm
T	23,812 mm
B	25,4 mm
C	19,05 mm
a	17,6 mm
Da	74 mm
B_	25.4
Db	77 mm
da	58 mm
Y0	0.99
db	51 mm
C0	99
D_	82.931
Z_	18
C_	19.05
Y1	1.8
DE_	71.678
SLR	18
D_a	74
DI_	54.477
DA1	9.237
DA2	8.283
CUP	0.203
DA_	8.762
D_b	77
RAr	173.558
SDM_	63.127
KBRG	3161

yobi	25590/25520
CONE	0.343
ALP21	25
ALP22	10
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	3
r min.	3,5 mm
LangID	1
Weight	0,546 Kg
ALPHA_	12.583
r1 min.	0,8 mm
ra max.	3,5 mm
Oil rpm	6000
outer r	0.8
hidYobi	25590/25520
GRS rpm	4500
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	0.8
ra1 max.	0,8 mm
Size (mm)	45.618x82.931x23.812
SHOG_yobi	25590R/25520R
Prod_Type3	TRBSR_ID_A
Width (mm)	23,812
Bearing number	25590/25520
Bore Diameter (mm)	45,618
Outer Diameter (mm)	82,931
Calculation factor (e)	0,33

(Oil) Lubrication Speed	6000 r/min
Calculation factor (Y0)	0,99
(Grease) Lubrication Speed	4500 r/min
Basic static load rating (C0)	99 kN
Basic dynamic load rating (C)	76,5 kN