



Bearing No. PCM 202320 M

D	23 mm
d	20 mm
B	20 mm
M	3 mm
c1 min	0,1 mm
c2 min	0,2 mm
Weight	0,013 Kg
Size (mm)	20x23x20
Width (mm)	20
Mass bushing	0.013 kg
groove type:	Plain Interior
? ±8	20 °
ground type:	Ground
bushing type:	Plain
Bearing number	PCM 202320 M
overall length:	23 mm
Tolerance shaft	h8
inside diameter:	20 mm
bushing material:	POM
Tolerance housing	H7
c ₁ min.	0.1 mm
c ₁ max.	0.7 mm
c ₂ min.	0.2 mm
c ₂ max.	1 mm
Bore Diameter (mm)	20
Outer Diameter (mm)	23
bushing outside diameter:	12 mm
overall outside diameter:	12 mm
Basic dynamic load rating (C)	46,5 kN

Specific dynamic load factor K	120 N/mm ²
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2.5 m/s
Coefficient of friction μ min.	0.02
Coefficient of friction μ max.	0.2
Specific static load factor K ₀	250 N/mm ²
Basic dynamic load rating - radial direction C	46.5 kN
Basic static load rating - radial direction C ₀	96.5 kN
Factor depending on material and bearing type K _M	1900