

Bearing No. 23984-K-MB + AH3984G-H

| | |
|-----------------|--|
| l | 130 mm |
| e | 0,18 |
| D | 560 mm |
| B | 106 mm |
| a | 8 mm |
| b | 22 mm |
| m | 72,1 kg / Weight |
| d | 420 mm |
| Size (mm) | 400x560x106 |
| Width (mm) | 106 |
| d _s | 9,5 mm |
| C _r | 1900000 N / Dynamic load rating (radial) |
| n _s | 17,7 mm |
| D ₁ | 519,5 mm |
| Y ₁ | 3,85 |
| Y ₂ | 5,73 |
| Y ₀ | 3,76 |
| n _G | 1230 1/min / Limiting speed |
| n _B | 670 1/min / Reference speed |
| m ₁ | 17,8 kg / Weight, withdrawal sleeve |
| C _{0r} | 4500000 N / Static load rating (radial) |
| Bearing number | 23984-K-MB + AH3984G-H |
| d _{1H} | 400 mm |
| d _{2G} | Tr440X5 |
| | |

| | |
|---|--|
| C_{ur} | 300000 N / Fatigue limit load, radial |
| r_{min} | 4 mm |
| $r_{a\ max}$ | 3 mm |
| $d_{a\ min}$ | 434,6 mm |
| $D_{a\ max}$ | 545,4 mm |
| Bore Diameter (mm) | 400 |
| Outer Diameter (mm) | 560 |
| - AH3984G-H / Designation, withdrawal sleeve | AH3984GH / Designation, withdrawal sleeve |