



Bearing No. LL225749/LL225710

e	0.33
d	127 mm
D	165,895 mm
T	18,258 mm
B	17,462 mm
C	13,495 mm
a	24,2 mm
Da	158 mm
B_	17.462
Db	160 mm
da	135 mm
Y0	0.99
db	132 mm
C0	149
D_	165.895
Z_	42
C_	13.495
Y1	1.8
DE_	155.002
SLR	11
D_a	158
DI_	137.739
DA1	9.554
DA2	9.266
CUP	0.288
DA_	8.862
D_b	160
RAr	364.934
SDM_	146.475
KBRG	3161

yobi	LL225749/LL225710
CONE	0.647
ALP21	25
ALP22	0
ALP23	0
BETA_	0
BET21	1
BET23	0
BET22	30
r min.	1,5 mm
LangID	1
Weight	0,935 Kg
ALPHA_	12.5
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	2600
outer r	1.5
hidYobi	LL225749/LL225710
GRS rpm	1900
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	127x165.895x18.258
SHOG_yobi	LL225749/LL225710
Prod_Type3	TRBSR_ID_A
Width (mm)	18,258
Bearing number	LL225749/LL225710
Bore Diameter (mm)	127
Outer Diameter (mm)	165,895
Calculation factor (e)	0,33

(Oil) Lubrication Speed	2600 r/min
Calculation factor (Y0)	0,99
(Grease) Lubrication Speed	1900 r/min
Basic static load rating (C0)	149 kN
Basic dynamic load rating (C)	84,5 kN