



Bearing No. 26112/26283

|                                 |              |
|---------------------------------|--------------|
| R                               | 1,5 mm       |
| d                               | 28,575 mm    |
| D                               | 72 mm        |
| T                               | 19 mm        |
| B                               | 18,923 mm    |
| C                               | 15,875 mm    |
| r                               | 1,5 mm       |
| Da                              | 65 mm        |
| Ab                              | 1,1 mm       |
| Aa                              | 0,6 mm       |
| Db                              | 62 mm        |
| da                              | 35 mm        |
| db                              | 37 mm        |
| a -                             | 4,1 mm       |
| Weight                          | 0,39 Kg      |
| Size (mm)                       | 28.575x72x19 |
| Width (mm)                      | 19           |
| Factor (K)                      | 1,62         |
| Factor (G1)                     | 16,1         |
| Factor (Cg)                     | 0,0148       |
| Factor (G2)                     | 10,1         |
| Bearing number                  | 26112/26283  |
| Bore Diameter (mm)              | 28,575       |
| Outer Diameter (mm)             | 72           |
| Calculation factor (e)          | 0,36         |
| Basic static load rating (C0)   | 60,1 kN      |
| Basic dynamic load rating (C1)  | 54,4 kN      |
| Basic dynamic load rating (C90) | 14,1         |
|                                 |              |

|                                  |     |
|----------------------------------|-----|
| Basic dynamic load rating (Ca90) | 8,7 |
|----------------------------------|-----|