




Bearing No. 26118/26283

e	0.36
d	30 mm
D	72 mm
T	19 mm
B	18,923 mm
C	15,875 mm
a	14,8 mm
Da	62 mm
B_	18.923
Db	65 mm
da	38 mm
Y0	0.92
db	36 mm
C0	56
D_	72
Z_	15
C_	15.875
Y1	1.7
DE_	59.21
SLR	13
D_a	62
DI_	41.755
DA1	9.289
DA2	8.388
CUP	0.163
DA_	8.842
D_b	65
RAr	133.096
SDM_	50.478
KBRG	3171

yobi	26118/26283
CONE	0.225
ALP21	27
ALP22	0
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	0
r min.	1,5 mm
LangID	1
Weight	0,388 Kg
ALPHA_	13.5
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	7500
outer r	1.5
hidYobi	26118/26283
GRS rpm	5600
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	30x72x19
SHOG_yobi	26118R/26283R
Prod_Type3	TRBSR_ID_A
Width (mm)	19
Bearing number	26118/26283
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Calculation factor (e)	0,36

(Oil) Lubrication Speed	7500 r/min
Calculation factor (Y0)	0,92
(Grease) Lubrication Speed	5600 r/min
Basic static load rating (C0)	56 kN
Basic dynamic load rating (C)	52 kN