



Bearing No. L68149/L68110

e	0.42
D	59,131 mm
C	11,938 mm
B	16,764 mm
T	15,875 mm
a	13,2 mm
d	35 mm
da	45,5 mm
D_	59.131
B_	16.764
Y1	1.4
Db	56 mm
db	39 mm
Da	52 mm
Z_	23
C0	47
C_	11.938
Y0	0.79
D_a	52
D_b	56
SLR	11
RAr	102.99
DE_	52.106
DI_	41.725
CUP	0.056
DA_	5.333
DA1	5.631
DA2	5.032
SDM_	46.95
CONE	0.117

KBRG	3171
yobi	L68149/L68110
ALP22	0
BETA_	1
BET23	0
BET22	8
BET21	3
ALP21	31
ALP23	0
LangID	1
ALPHA_	15.5
Weight	0,173 Kg
Oil rpm	8000
hidYobi	L68149/L68110
inner r	SPEC
ra max.	3,5 mm
outer r	1.3
GRS rpm	6000
r1 min.	1,3 mm
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	35x59.131x15.875
SHOG_yobi	L68149R/L68110R
Prod_Type3	TRBSR_ID_A
Width (mm)	15,875
Bearing number	L68149/L68110
Bore Diameter (mm)	35
Outer Diameter (mm)	59,131
Calculation factor (e)	0,42
Calculation factor (Y0)	0,79

(Oil) Lubrication Speed	8000 r/min
(Grease) Lubrication Speed	6000 r/min
Basic dynamic load rating (C)	35 kN
Basic static load rating (C0)	47 kN