



Bearing No. 60/22LLU

C	12 mm
d	22 mm
D	44 mm
B	12 mm
Bore	0.866 Inch 22 Millimeter
Noun	Bearing
Weight	0,074 Kg
da max	26,5 mm
UNSPSC	31171504
r min.	0,6 mm
da min.	26 mm
ra max.	0,6 mm
series:	60
Da max.	40 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	22x44x12
Inventory	0.0
Snap Ring	No
Width (mm)	12
bore type:	Round
maximum rpm:	20000 RPM
Weight / LBS	0.163
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	22 mm
Keyword String	Ball

overall width:	12 mm
cage material:	Steel
fillet radius:	0.6 mm
Bearing number	60/22LLU
Enclosure Type	Contact Seal
Reference speed	10 000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	1.732 Inch 44 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Long Description	22MM Bore; 44MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.472 Inch 12 Millimeter
outside diameter:	44 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.075
inner ring width:	12 mm
outer ring width:	12 mm
Manufacturer Name	NTN
Bore Diameter (mm)	22
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	44

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	10000 rpm
static load capacity:	5050 N
dynamic load capacity:	9400 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	60/22LLU/2A
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	5,05 kN
Basic dynamic load rating (C)	9,4 kN
Maximum Capacity / Filling Slot	No