



Bearing No. 23952-MB

|                     |                                         |
|---------------------|-----------------------------------------|
| m                   | 24,1 kg / Weight                        |
| d                   | 260 mm                                  |
| D                   | 360 mm                                  |
| B                   | 75 mm                                   |
| e                   | 0,19                                    |
| Size (mm)           | 260x360x75                              |
| Width (mm)          | 75                                      |
| $n_s$               | 15 mm                                   |
| $Y_1$               | 3,54                                    |
| $Y_2$               | 5,27                                    |
| $D_1$               | 330,5 mm                                |
| $d_s$               | 8 mm                                    |
| $Y_0$               | 3,46                                    |
| $n_G$               | 2100 1/min / Limiting speed             |
| $n_B$               | 1200 1/min / Reference speed            |
| $C_r$               | 930000 N / Dynamic load rating (radial) |
| $C_{0r}$            | 1930000 N / Static load rating (radial) |
| Bearing number      | 23952-MB                                |
| $C_{ur}$            | 108000 N                                |
| $r_{min}$           | 2,1 mm                                  |
| $r_{a \max}$        | 2,1 mm                                  |
| $d_{a \min}$        | 270,2 mm                                |
| $D_{a \max}$        | 349,8 mm                                |
| Bore Diameter (mm)  | 260                                     |
| Outer Diameter (mm) | 360                                     |

