



Bearing No. 26884R/26822

|                               |                      |
|-------------------------------|----------------------|
| B                             | 25,4 mm              |
| d                             | 42,875 mm            |
| D                             | 79,375 mm            |
| T                             | 23,812 mm            |
| C                             | 19,05 mm             |
| a                             | 16,1 mm              |
| Db                            | 74 mm                |
| Da                            | 71 mm                |
| r min.                        | 3,6 mm               |
| Weight                        | 0,5 Kg               |
| db min                        | 48,5 mm              |
| da min.                       | 55 mm                |
| r2 min.                       | 0,8 mm               |
| rb max.                       | 0,8 mm               |
| ra max.                       | 3,6 mm               |
| Size (mm)                     | 42.875x79.375x23.812 |
| Width (mm)                    | 23,812               |
| Bearing number                | 26884R/26822         |
| Bore Diameter (mm)            | 42,875               |
| Outer Diameter (mm)           | 79,375               |
| Calculation factor (e)        | 0,32                 |
| (Oil) Lubrication Speed       | 6700 r/min           |
| Calculation factor (Y0)       | 1,04                 |
| (Grease) Lubrication Speed    | 5000 r/min           |
| Basic dynamic load rating (C) | 81,1 kN              |
| Basic static load rating (C0) | 105 kN               |