




Bearing No. 02872/02820

e	0.45
d	28,575 mm
D	73,025 mm
T	22,225 mm
B	22,225 mm
C	17,462 mm
a	18,3 mm
Da	62 mm
B_	22.225
Db	68 mm
da	37,5 mm
Y0	0.73
db	37 mm
C0	64.5
D_	73.025
Z_	16
C_	17.462
Y1	1.3
DE_	61.628
SLR	15
D_a	62
DI_	46.09
DA1	8.63
DA2	7.502
CUP	0.16
DA_	8.069
D_b	68
RAr	114.139
SDM_	54.001
KBRG	3161

yobi	02872/02820
CONE	0.321
ALP21	33
ALP22	40
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	20
r min.	0,8 mm
LangID	1
Weight	0,481 Kg
ALPHA_	16.833
r1 min.	3,3 mm
ra max.	0,8 mm
Oil rpm	7100
outer r	3.3
hidYobi	02872/02820
GRS rpm	5300
inner r	0.8
hidTable	ecat_NSTPRI
inner ra	0.8
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	28.575x73.025x22.225
SHOG_yobi	02872R/02820R
Prod_Type3	TRBSR_ID_A
Width (mm)	22,225
Bearing number	02872/02820
Bore Diameter (mm)	28,575
Outer Diameter (mm)	73,025
Calculation factor (e)	0,45

(Oil) Lubrication Speed	7100 r/min
Calculation factor (Y0)	0,73
(Grease) Lubrication Speed	5300 r/min
Basic static load rating (C0)	64,5 kN
Basic dynamic load rating (C)	54,5 kN