



Bearing No. 6001

D	28 mm
d	12 mm
B	8 mm
C	8 mm
r	0.3
Z_	8
B_	8
D_	28
ra	0.3
C0	2.37
fo	13
DI_	15.238
SRI	2.46
D_a	26
DE_	24.762
DA_	4.762
SRE	2.46
SRIN	-0.015
mass	0.022
Noun	Bearing
SRIX	0.015
SREN	-0.015
Bore	0.472 Inch 12 Millimeter
KBRG	6101
SREX	0.015
bomp	0
SDM_	20
yobi	6001
SBRG	10

UNSPSC	31171504
LangID	1
r min.	0,3 mm
da min	14
C_conv	5100
ALPHA_	0
Weight	0,022 Kg
da max	15,5 mm
Da max.	26 mm
da min.	14 mm
Oil rpm	32000
GRS rpm	28000
ra max.	0,3 mm
hidYobi	6001
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	12x28x8
Snap Ring	No
Enclosure	Open
Width (mm)	8
Prod_Type3	DGBB_SR_OT
Weight / LBS	0.05
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6001
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.315 Inch 8 Millimeter

Outside Diameter	1.102 Inch 28 Millimeter
Long Description	12MM Bore; 28MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Weight / Kilogram	0.02
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	12
Outer Diameter (mm)	28
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	32 000 r/min
Manufacturer Item Number	6001
Internal Special Features	No
(Grease) Lubrication Speed	28 000 r/min
Basic static load rating (C0)	2,37 kN
Basic dynamic load rating (C)	5,1 kN
Maximum Capacity / Filling Slot	No