



Bearing No. 6001-2RS

| | |
|------------------|----------------------------|
| D | 28 mm |
| d | 12 mm |
| B | 8 mm |
| C | 8 mm |
| Bore | 0.472 Inch 12 Millimeter |
| Noun | Bearing |
| da max | 15 mm |
| UNSPSC | 31171504 |
| Weight | 0,022 Kg |
| r min. | 0,3 mm |
| ra max. | 0,3 mm |
| Da max. | 26 mm |
| da min. | 14 mm |
| Category | Single Row Ball Bearing |
| Snap Ring | No |
| Inventory | 0.0 |
| Size (mm) | 12x28x8 |
| Enclosure | 2 Seals |
| Width (mm) | 8 |
| Weight / LBS | 0.054 |
| Inch - Metric | Metric |
| Cage Material | Steel |
| Product Group | F02352 |
| Keyword String | Ball |
| Enclosure Type | Contact Seal |
| Bearing number | 6001-2RS |
| Precision Class | ABEC 1 ISO P0 |
| Rolling Element | Ball Bearing |
| Outside Diameter | 1.102 Inch 28 Millimeter |

| | |
|---------------------------------|--|
| Long Description | 12MM Bore; 28MM Outside Diameter; 8MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Outer Race Width | 0.315 Inch 8 Millimeter |
| Manufacturer URL | http://www.koyousa.com |
| Weight / Kilogram | 0.03 |
| Manufacturer Name | KOYO |
| Internal Clearance | C0-Medium |
| Bore Diameter (mm) | 12 |
| Outer Diameter (mm) | 28 |
| Minimum Buy Quantity | N/A |
| Harmonized Tariff Code | 8482.10.50.68 |
| Manufacturer Item Number | 6001 2RS |
| Internal Special Features | No |
| (Grease) Lubrication Speed | 17000 r/min |
| Basic static load rating (C0) | 2,4 kN |
| Basic dynamic load rating (C) | 5,1 kN |
| Maximum Capacity / Filling Slot | No |