



Bearing No. 6001DDU

| | |
|------|-------------------------------|
| r | 0.3 |
| d | 12 mm |
| D | 28 mm |
| B | 8 mm |
| C | 8 mm |
| fo | 13 |
| D_ | 28 |
| B_ | 8 |
| ra | 0.3 |
| Z_ | 8 |
| C0 | 2.37 |
| DI_ | 15.238 |
| SRE | 2.46 |
| D_a | 26 |
| DE_ | 24.762 |
| SRI | 2.46 |
| DA_ | 4.762 |
| SREN | -0.015 |
| Bore | 0.472 Inch 12 Millimeter |
| SRIN | -0.015 |
| bomp | 0 |
| SRIX | 0.015 |
| yobi | 6001DDU |
| mass | 0.022 |
| SDM_ | 20 |
| KBRG | 6161 |
| SREX | 0.015 |
| SBRG | 10 |
| Noun | Bearing |
| | |

| | |
|------------------|---------------------------|
| da max | 15,5 mm |
| Weight | 0,022 Kg |
| LangID | 1 |
| r min. | 0,3 mm |
| da min | 14 |
| ALPHA_ | 0 |
| C_conv | 5100 |
| UNSPSC | 31171504 |
| da min. | 14 mm |
| hidYobi | 6001DDU |
| GRS rpm | 18000 |
| Da max. | 26 mm |
| ra max. | 0,3 mm |
| Category | Single Row Ball Bearing |
| hidTable | ecat_NSRDGB |
| Snap Ring | No |
| Enclosure | 2 Seals |
| Size (mm) | 12x28x8 |
| Inventory | 0.0 |
| Prod_Type3 | DGBB_SR_DD |
| Width (mm) | 8 |
| Weight / LBS | 0.04804 |
| Product Group | B00308 |
| Inch - Metric | Metric |
| Cage Material | Steel |
| Bearing number | 6001DDU |
| Enclosure Type | Contact Seal |
| Other Features | Deep Groove Rubber Seal |
| Keyword String | Ball |
| Rolling Element | Ball Bearing |
| Precision Class | ABEC 1 ISO P0 |
| Outer Race Width | 0.315 Inch 8 Millimeter |

| | |
|---------------------------------|--|
| Inner Race Width | 0 Inch 0 Millimeter |
| Long Description | 12MM Bore; 28MM Outside Diameter; 8MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C |
| Manufacturer URL | http://www.nskamericas.com |
| Outside Diameter | 1.102 Inch 28 Millimeter |
| Weight / Kilogram | 0.022 |
| Manufacturer Name | NSK |
| Internal Clearance | C0-Medium |
| Bore Diameter (mm) | 12 |
| Outer Diameter (mm) | 28 |
| Minimum Buy Quantity | N/A |
| Harmonized Tariff Code | 8482.10.50.68 |
| Internal Special Features | No |
| (Grease) Lubrication Speed | 18 000 r/min |
| Basic dynamic load rating (C) | 5,1 kN |
| Basic static load rating (C0) | 2,37 kN |
| Maximum Capacity / Filling Slot | No |