



Bearing No. 6001VV

D	28 mm
d	12 mm
B	8 mm
C	8 mm
r	0.3
Z_	8
B_	8
D_	28
ra	0.3
C0	2.37
fo	13
DI_	15.238
SRI	2.46
D_a	26
DE_	24.762
DA_	4.762
SRE	2.46
SRIN	-0.015
SBRG	10
yobi	6001VV
SDM_	20
SREX	0.015
KBRG	6151
bomp	0
mass	0.022
Bore	0.472 Inch 12 Millimeter
SRIX	0.015
SREN	-0.015
Noun	Bearing

ALPHA_	0
da min	14
LangID	1
r min.	0,3 mm
UNSPSC	31171504
da max	15,5 mm
C_conv	5100
Weight	0,022 Kg
ra max.	0,3 mm
hidYobi	6001VV
GRS rpm	28000
da min.	14 mm
Da max.	26 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	12x28x8
Enclosure	2 Seals
Inventory	0.0
Width (mm)	8
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.05
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6001VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	1.102 Inch 28 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter

Long Description	12MM Bore; 28MM Outside Diameter; 8MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.02
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	12
Outer Diameter (mm)	28
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6001VV
Internal Special Features	No
(Grease) Lubrication Speed	28 000 r/min
Basic static load rating (C0)	2,37 kN
Basic dynamic load rating (C)	5,1 kN
Maximum Capacity / Filling Slot	No