



Bearing No. X32305/Y32305

|                                 |               |
|---------------------------------|---------------|
| R                               | 1,5 mm        |
| d                               | 25 mm         |
| D                               | 62 mm         |
| T                               | 25,25 mm      |
| B                               | 24 mm         |
| C                               | 20 mm         |
| r                               | 1,5 mm        |
| Da                              | 57 mm         |
| Ab                              | 2,3 mm        |
| Aa                              | 2,2 mm        |
| Db                              | 54 mm         |
| da                              | 31,5 mm       |
| db                              | 35 mm         |
| a -                             | 9,7 mm        |
| Weight                          | 0,37 Kg       |
| Size (mm)                       | 25x62x25.25   |
| Width (mm)                      | 25,25         |
| Factor (K)                      | 1,95          |
| Factor (G1)                     | 15,1          |
| Factor (Cg)                     | 0,0134        |
| Factor (G2)                     | 7,2           |
| Bearing number                  | X32305/Y32305 |
| Bore Diameter (mm)              | 25            |
| Outer Diameter (mm)             | 62            |
| Calculation factor (e)          | 0,3           |
| Basic static load rating (C0)   | 72,4 kN       |
| Basic dynamic load rating (C1)  | 67,1 kN       |
| Basic dynamic load rating (C90) | 17,4          |

|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 8,93 |
|----------------------------------|------|