



Bearing No. 2877/2820

e	0.37
d	34,925 mm
D	73,025 mm
T	22,225 mm
B	23,812 mm
C	17,462 mm
a	16,1 mm
Da	63 mm
B_	23.812
Db	68 mm
da	47 mm
Y0	0.9
db	41,5 mm
C0	77
D_	73.025
Z_	17
C_	17.462
Y1	1.6
DE_	62.352
SLR	16
D_a	63
DI_	45.823
DA1	8.877
DA2	7.857
CUP	0.15
DA_	8.37
D_b	68
RAr	138.739
SDM_	54.067
KBRG	3161

yobi	2877/2820
CONE	0.291
ALP21	27
ALP22	32
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	40
r min.	3,5 mm
LangID	1
Weight	0,441 Kg
ALPHA_	13.767
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	7100
outer r	3.3
hidYobi	2877/2820
GRS rpm	5300
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	34.925x73.025x22.225
SHOG_yobi	2877R/2820R
Prod_Type3	TRBSR_ID_A
Width (mm)	22,225
Bearing number	2877/2820
Bore Diameter (mm)	34,925
Outer Diameter (mm)	73,025
Calculation factor (e)	0,37

(Oil) Lubrication Speed	7100 r/min
Calculation factor (Y0)	0,9
(Grease) Lubrication Speed	5300 r/min
Basic static load rating (C0)	77 kN
Basic dynamic load rating (C)	63,5 kN