



**Bearing No. NUP304EG**

C	15 mm
B	15 mm
D	52 mm
d	20 mm
Fw	27,5 mm
r1	0.6 mm
Width	15 mm
r min.	1,1 mm
Weight	0,15 Kg
r1 min.	0,6 mm
dd (min)	33 mm
Da (max)	45 mm
dc (min)	30 mm
db (max)	27 mm
db (min)	25 mm
ra (max)	1 mm
Bore Size	20 mm
ra1 (max)	0.6 mm
Bore Type	Cylindrical Bore
Size (mm)	20x52x15
Enclosure	Open
Width (mm)	15
Configuration	Single Row
Bearing number	NUP304EG
Outside Diameter	52 mm
Radial Clearance	0.020 to 0.045 mm
Static Load Rating	26,900 N
Bore Diameter (mm)	20
Dynamic Load Rating	31,500 N
Outer Diameter (mm)	52

Limiting Speed - Oil	15,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	12,000 rpm
(Grease) Lubrication Speed	12000 r/min
Inside Ring Outside Diameter	27.5 mm
Basic static load rating (C0)	26,9 kN
Basic dynamic load rating (C)	31,5 kN