



Bearing No. 22338-E1-K-T41A + H2338

|                |                                          |
|----------------|------------------------------------------|
|                | H2338 / Adapter sleeve                   |
| m              | 77,2 kg / Weight                         |
| B              | 132 mm                                   |
| l              | 169 mm                                   |
| d              | 190 mm                                   |
| c              | 31 mm                                    |
| e              | 0,34                                     |
| D              | 400 mm                                   |
| Size (mm)      | 170x400x132                              |
| Width (mm)     | 132                                      |
| $Y_1$          | 1,96                                     |
| $Y_2$          | 2,92                                     |
| $D_1$          | 338,1 mm                                 |
| $D_m$          | 240 mm                                   |
| $d_2$          | 236,8 mm                                 |
| $C_r$          | 2220000 N / Dynamic load rating (radial) |
| $d_s$          | 12,5 mm                                  |
| $Y_0$          | 1,92                                     |
| $n_s$          | 23,5 mm                                  |
| $m_1$          | 12,9 kg                                  |
| $n_G$          | 1940 1/min / Limiting speed              |
| $C_{0r}$       | 2650000 N / Static load rating (radial)  |
| Bearing number | 22338-E1-K-T41A + H2338                  |
| $d_{1H}$       | 170 mm                                   |
| $r_{min}$      | 5 mm                                     |
|                |                                          |

|                     |        |
|---------------------|--------|
| $r_{a\ max}$        | 4 mm   |
| $d_{a\ max}$        | 228 mm |
| $D_{a\ max}$        | 380 mm |
| $B_{a\ min}$        | 9 mm   |
| $d_{b\ min}$        | 206 mm |
| Bore Diameter (mm)  | 170    |
| Outer Diameter (mm) | 400    |