



Bearing No. JM734449/JM734410

e	0.44
d	170 mm
D	240 mm
T	46 mm
B	44,5 mm
C	37 mm
a	50,5 mm
Da	222 mm
B_	44.5
Db	232 mm
da	185 mm
Y0	0.75
db	180 mm
C0	720
D_	240
Z_	32
C_	37
Y1	1.4
DE_	220.584
SLR	35
D_a	222
DI_	187.162
DA1	17.953
DA2	16.431
CUP	2.02
DA_	17.194
D_b	232
RAr	411.5
SDM_	203.949
KBRG	3141

yobi	JM734449/JM734410
CONE	4.42
ALP21	32
ALP22	30
ALP23	0
BETA_	1
BET21	2
BET23	0
BET22	30
r min.	3 mm
LangID	1
Weight	6,44 Kg
ALPHA_	16.25
r1 min.	2,5 mm
ra max.	3 mm
Oil rpm	1800
outer r	2.5
hidYobi	JM734449/JM734410
GRS rpm	1300
inner r	3
hidTable	ecat_NSTPRI
inner ra	3
outer rb	2.5
ra1 max.	2,5 mm
Size (mm)	170x240x46
SHOG_yobi	JM734449R/JM734410 R
Prod_Type3	TRBSR_ID_A
Width (mm)	46
Bearing number	JM734449/JM734410
Bore Diameter (mm)	170
Outer Diameter (mm)	240
Calculation factor (e)	0,44

(Oil) Lubrication Speed	1800 r/min
Calculation factor (Y0)	0,75
(Grease) Lubrication Speed	1300 r/min
Basic static load rating (C0)	720 kN
Basic dynamic load rating (C)	380 kN