



Bearing No. C6006V

D	55 mm
C	45 mm
B	45 mm
d	30 mm
D1	47,3 mm
S2	4,9 mm
d2	38,5 mm
S1	7,9 mm
Weight	0,49 Kg
da max	43 mm
weight:	1.08 lbs
r1 min.	1 mm
r2 min.	1 mm
da min.	34,6 mm
Da max.	50,4 mm
ra max.	1 mm
Size (mm)	30x55x45
Width (mm)	45
bore type:	Straight
maximum rpm:	3200 rpm
closure type:	Open
overall width:	45 mm
fillet radius:	1 mm
bore diameter:	30 mm
cage material:	Steel
Bearing number	C6006V
Limiting speed	3200 r/min
Reference speed	– r/min
precision rating:	Not Rated
outer ring width:	45 mm

outside diameter:	55 mm
Bore Diameter (mm)	30
lubrication holes:	No Holes
Outer Diameter (mm)	55
static load capacity:	180 kN
dynamic load capacity:	134 kN
Calculation factor (k2)	0,096
Fatigue load limit (Pu)	21,2
manufacturer upc number:	7316570933710
manufacturer product page:	Click here
operating temperature range:	392 °F
Basic static load rating (C0)	180 kN
Basic dynamic load rating (C)	134 kN