



Bearing No. 238/600-K-MB

|                     |                                          |
|---------------------|------------------------------------------|
| D                   | 730 mm                                   |
| d                   | 600 mm                                   |
| B                   | 98 mm                                    |
| e                   | 0,12                                     |
| m                   | 84 kg / Weight                           |
| Size (mm)           | 600x730x98                               |
| Width (mm)          | 98                                       |
| $n_G$               | 980 1/min / Limiting speed               |
| $Y_0$               | 5,65                                     |
| $Y_2$               | 8,61                                     |
| $Y_1$               | 5,78                                     |
| $C_r$               | 1960000 N / Dynamic load rating (radial) |
| $n_s$               | 12,2 mm                                  |
| $D_1$               | 696,3 mm                                 |
| $d_s$               | 6,3 mm                                   |
| $C_{0r}$            | 5300000 N / Static load rating (radial)  |
| $C_{ur}$            | 350000 N / Fatigue limit load, radial    |
| Bearing number      | 238/600-K-MB                             |
| $r_{min}$           | 3 mm                                     |
| $r_{a \max}$        | 2,5 mm                                   |
| $d_{a \min}$        | 612,4 mm                                 |
| $D_{a \max}$        | 717,6 mm                                 |
| Bore Diameter (mm)  | 600                                      |
| Outer Diameter (mm) | 730                                      |