



Bearing No. 53236XU

C	284
D	250 mm
R	200 mm
A	112 mm
T	66 mm
b	21,5 mm
d	180 mm
r	1.5
A_	112
D_	250
Z_	24
da	222
T3	58.2
C0	955
T4	66
ra	1.5
B_	66
R_	200
D2	210 mm
D3	260 mm
D1	183 mm
d1	247 mm
D_2	210
D_3	260
SRE	13.7
D_1	183
SRI	13.7
DA_	25.4
D_a	208
SREX	0.1

SRIN	0
SREN	0
mass	10.8
yobi	53236XU
SDM_	215
SRIX	0.1
KBRG	5131
r min.	1,5 mm
LangID	1
Weight	10,8 Kg
ra max.	1,5 mm
GRS rpm	800
Oil rpm	1200
da min.	222 mm
Da max.	208 mm
hidYobi	53236XU
hidTable	ecat_NSSDTB
Size (mm)	180x250x66
Prod_Type3	TB_SD_WASW
Width (mm)	66
Bearing number	53236XU
Bore Diameter (mm)	180
Outer Diameter (mm)	250
(Grease) Lubrication Speed	800 r/min
Basic static load rating (C0)	955 kN
Basic dynamic load rating (C)	284 kN