



Bearing No. JLM104948/JLM104910

e	0.31
d	50 mm
D	82 mm
T	21,5 mm
B	21,5 mm
C	17 mm
a	16,1 mm
Da	76 mm
B_	21.5
Db	78 mm
da	60 mm
Y0	1.1
db	55 mm
C0	96
D_	82
Z_	21
C_	17
Y1	2
DE_	74.055
SLR	16
D_a	76
DI_	58.103
DA1	8.455
DA2	7.759
CUP	0.129
DA_	8.108
D_b	78
RAr	193.8
SDM_	66.124
KBRG	3141

yobi	JLM104948/JLM104910
CONE	0.306
ALP21	23
ALP22	0
ALP23	0
BETA_	1
BET21	2
BET23	0
BET22	30
r min.	3 mm
LangID	1
Weight	0,435 Kg
ALPHA_	11.5
r1 min.	0,5 mm
ra max.	3 mm
Oil rpm	5600
outer r	0.5
hidYobi	JLM104948/JLM104910
GRS rpm	4300
inner r	3
hidTable	ecat_NSTPRI
inner ra	3
outer rb	0.5
ra1 max.	0,5 mm
Size (mm)	50x82x21.5
SHOG_yobi	JLM104948R/910R
Prod_Type3	TRBSR_ID_A
Width (mm)	21,5
Bearing number	JLM104948/JLM104910
Bore Diameter (mm)	50
Outer Diameter (mm)	82
Calculation factor (e)	0,31

(Oil) Lubrication Speed	5600 r/min
Calculation factor (Y0)	1,1
(Grease) Lubrication Speed	4300 r/min
Basic static load rating (C0)	96 kN
Basic dynamic load rating (C)	71 kN