



Bearing No. JHM534149/JHM534110

|      |         |
|------|---------|
| e    | 0.38    |
| d    | 170 mm  |
| D    | 230 mm  |
| T    | 39 mm   |
| B    | 38 mm   |
| C    | 31 mm   |
| a    | 43,2 mm |
| Da   | 217 mm  |
| B_   | 38      |
| Db   | 224 mm  |
| da   | 184 mm  |
| Y0   | 0.86    |
| db   | 178 mm  |
| C0   | 520     |
| D_   | 230     |
| Z_   | 32      |
| C_   | 31      |
| Y1   | 1.6     |
| DE_  | 214.486 |
| SLR  | 28.5    |
| D_a  | 217     |
| DI_  | 185.064 |
| DA1  | 15.627  |
| DA2  | 14.634  |
| CUP  | 1.3     |
| DA_  | 15.132  |
| D_b  | 224     |
| RAr  | 447.7   |
| SDM_ | 199.921 |
| KBRG | 3141    |
|      |         |

|                    |                     |
|--------------------|---------------------|
| yobi               | JHM534149/JHM534110 |
| CONE               | 3.1                 |
| ALP21              | 28                  |
| ALP22              | 40                  |
| ALP23              | 0                   |
| BETA_              | 1                   |
| BET21              | 2                   |
| BET23              | 0                   |
| BET22              | 0                   |
| r min.             | 3 mm                |
| LangID             | 1                   |
| Weight             | 4,4 Kg              |
| ALPHA_             | 14.333              |
| r1 min.            | 2,5 mm              |
| ra max.            | 3 mm                |
| Oil rpm            | 1800                |
| outer r            | 2.5                 |
| hidYobi            | JHM534149/JHM534110 |
| GRS rpm            | 1300                |
| inner r            | 3                   |
| hidTable           | ecat_NSTPRI         |
| inner ra           | 3                   |
| outer rb           | 2.5                 |
| ra1 max.           | 2,5 mm              |
| Size (mm)          | 170x230x39          |
| SHOG_yobi          | JHM534149R/110R     |
| Prod_Type3         | TRBSR_ID_A          |
| Width (mm)         | 39                  |
| Bearing number     | JHM534149/JHM534110 |
| Bore Diameter (mm) | 170                 |
|                    |                     |

|                               |            |
|-------------------------------|------------|
| Outer Diameter (mm)           | 230        |
| Calculation factor (e)        | 0,38       |
| (Oil) Lubrication Speed       | 1800 r/min |
| Calculation factor (Y0)       | 0,86       |
| (Grease) Lubrication Speed    | 1300 r/min |
| Basic static load rating (C0) | 520 kN     |
| Basic dynamic load rating (C) | 278 kN     |